


FSP StarPro

Racing Valve Springs

Erson's Professional FSP Damperless Valve Springs have set the standard in the performance spring market. Engineered for maximum performance and durability, each set of 16 is quality-inspected, matched and tested to out-perform any other steel valve spring in the industry. Longer life, more laps, BEST VALUE!




New Applications!

- E915042** → Ideal for small block Chevy high-lift, high RPM oval track/drag race applications
- E915045** → LS1 high-lift Hydraulic Roller
- E915047** → Drag race high-lift, high-load application with shorter installed height

**OVAL TRACK
ENDURANCE
DRAG RACING
MOTORCYCLE**

PART#	O.D.	I.D.	Seat Pressure	Open Pressure	Coil Bind	Spring Rate	Max Lift
E915046 single	1.255	.830	115#@1.750"	350#@1.175"	1.100	409#	.600
E915042 dual	1.580	.828	249#@2.050"	650#@1.270"	1.200	541#	.800
E915043 dual	1.580	.832	235#@1.950"	610#@1.250"	1.170	536#	.730
E915044 dual	1.610	.842	235#@2.050"	645#@1.300"	1.220	547#	.780
E915045 dual	1.290	.945	155#@1.810"	405#@1.150"	1.100	450#	.660
E915160 dual	1.640	.860	250#@2.000"	803#@1.150"	1.070	650#	.880
E915170 dual	1.640	.860	280#@2.100"	794#@1.250"	1.150	605#	.900
E915047 triple	1.675	.874	350#@2.000"	900#@1.270"	1.200	700#	.730
E915048 triple	1.677	.635	346#@2.100"	1014#@1.200"	1.142	742#	.900
E915049 triple	1.677	.632	346#@2.200"	1073#@1.200"	1.142	728#	1.005
E915050 triple	1.667	.632	375#@2.200"	1145#@1.200"	1.142	770#	1.005
E915055 triple	1.667	.635	415#@2.300"	1215#@1.250"	1.180	765#	1.070



www.pbmperformance.com

WE ACCEPT



ERSON TECH LINE
800-641-7920

*Serving Racing Professionals
Worldwide for Decades*

7301 Global Drive/Louisville, KY 40258
800-588-9608